

Size	PR	Rim	Tread Depth (mm)	Tube Type	Inflated Dimensions (mm)		Max Load (kg)	Inflation Pressure (kpa)
					SW	OD	25km/h	25km/h
							Drive*Steer	Drive*Steer
5.00-8	8	3.50D	10	TT	137	470	1000*845	790
	10	3.50D	10	TT	137	470	1150*970	1000
18x7-8 (180/70-8)	14	4.33R	10	TT	173	465	1505*1270	970
	16	4.33R	10	TT	173	465	1695*1450	1000
6.00-9	10	4.00E	10	TT	160	540	1505*1270	860
6.50-10	10	5.00F	11	TT	175	590	1655*1400	790
7.00-12	12	5.00S	14	TT	190	676	2375*2005	860
8.25-12	12	7.00	15	TT	235	765	3060*2585	720
7.00-15	12	5.50F	15	TT	200	750	2870*2420	860
7.50-15	12	6.00	16	TT	215	780	3075*2680	790
7.50-16	12	6.00G	18	TT	215	805	3195*2700	790
	14	6.00G	18	TT	215	805	3535*2995	925
	16	6.00G	18	TT	215	805	3875*3280	1000
8.15-15 (28x9-15)	12	7.00	17	TT	215	704	2790*2355	830
	14	7.00	17	TT	215	704	3050*2575	970
9.00-20	18	7.00	22	TT	259	1018	4685*2970	860
10.00-20 (290/95-20)	18	7.50	23	TT	280	1055	5195*3365	860
	20	7.50	23	TT	280	1055	6275*4815	930
	24	7.50	23	TT	280	1055	7385*5670	1025
12.00-20 (330/95-20)	20	8.50	24	TT	315	1125	6835*4200	860
	24	8.50	24	TT	315	1125	7650*4780	930
	28	8.50	24	TT	315	1125	8510*5460	1025
250-15 (250/70-15)	16	7.50	20	TT	250	735	4355*3350	825
	18	7.50	20	TT	250	735	4745*3650	950
	20	7.50	20	TT	250	735	5135*3950	1075
300-15 (315/70-15)	18	8.00	22	TT	300	840	5850*4500	850
	20	8.00	22	TT	300	840	6500*5000	900