



| 承载能力 CAPACITY@ LOAD CENTER | 安装等级 MOUNTING CLASS | 最小叉架宽 MIN TRUCK CARRIAGE WIDTH | 框架宽度 CARRIAGE WIDTH | 垂直重心 VERTICAL CENTER OF GRAVITY | 自重 WEIGHT | 失载距 EFFECTIVE THICKNESS | 水平重心 HORIZONTAL CENTER OF GRAVITY |
|----------------------------------|---------------------------|---|---------------------------|--|--------------|-------------------------------|--|
| (kg@mm) | | mm | W (mm) | VCG (mm) | (kg) | ET (mm) | HCG (mm) |
| 2500@600 | II | 785 | 920 | 227 | 48.4 | 64 | 26 |
| 2500@600 | II | 895 | 970 | 229 | 50.5 | 64 | 26 |
| 2500@600 | II | 895 | 1020 | 228 | 52.2 | 64 | 26 |
| 2500@600 | II | 895 | 1040 | 228 | 52.9 | 64 | 26 |
| 2500@600 | II | 895 | 1070 | 230 | 54.2 | 64 | 26 |
| 2500@600 | II | 955 | 1100 | 229 | 55 | 64 | 26 |
| 2500@600 | II | 1040 | 1200 | 231 | 59.1 | 64 | 26 |
| 3500@600 | III | 865 | 970 | 302 | 62.4 | 64 | 32 |
| 3500@600 | III | 935 | 1070 | 303 | 66.9 | 64 | 32 |
| 3500@600 | III | 935 | 1100 | 304 | 68 | 64 | 32 |
| 3500@600 | III | 1035 | 1150 | 305 | 70.8 | 64 | 32 |
| 3500@600 | III | 1035 | 1200 | 305 | 72.7 | 64 | 32 |
| 3500@600 | III | 1035 | 1245 | 305 | 74.5 | 64 | 32 |
| 3500@600 | III | 1035 | 1300 | 305 | 76.7 | 64 | 32 |
| 3500@600 | III | 1035 | 1350 | 305 | 78.7 | 64 | 32 |